

HackberryPi CM5

An ultra portable handheld Linux device using Raspberry CM5 unit as Core with 4" 720x720 TFT Touch display and the original blackberry keyboard.

Specifications

Compute Device	Raspberry Pi CM5 (lite)
Display	4" 720x720 TFT with multi-touch
Battery	internal 5000mAh LiPo
Connectivity	2x USB 2.0 HDMI on-board Stemma I2C port for external sensors
Storage	micro SD card internal M.2 NVMe (optional)
Communication	onboard Wifi (optional external antenna) onboard Bluetooth

Common issues

CM5 with eMMC

The Raspberry Pi CM5 comes in many variations, with the options of having integrated eMMC storage, onboard bluetooth and wifi, and different amounts of RAM.

The CM5 versions with integrated eMMC storage need to be flashed with an adapter to enable boot from another medium (USB, NVMe, micro SD card,...). It is therefore recommended to get a CM5 lite (without eMMC).

Lacking hardware support

Some operating systems (like [Ubuntu](#) and [DragonOS](#) lack the hardware support for the CM5 (lite) and/or are running very unstably. For more details, refer to the respective [operating system's](#) page.

From:
<https://hackberry.cyberr.space/> - **Hackberry**

Permanent link:
<https://hackberry.cyberr.space/doku.php?id=hbcm5&rev=1749217030>

Last update: **2025/06/06 13:37**

